

TWISTER

TRIM SAVER

Maximize Profit Without Wasting Your Trim



w/o Trim Saver



w/ Trim Saver



WATCH IT IN ACTION

TWISTERTRIMMER.COM/TWISTER-TRIM-SAVER



Trim Saver Features

- FDA approved stainless steel bin
- FDA approved lid & fasteners
- FDA approved silicone bin lid seal
- FDA approved silicone cyclone gaskets



TWISTER

T2 TRIM SAVER



ADDITIONAL REQUIREMENTS

Extension Cord

12 AWG (Minimum AWG Size)

7.6m / 25ft max length

CONNECTOR (PLUG)

NEMA 6-20P



CS-18 T2 TRIM SAVER SPECIFICATIONS

Product Number	23-0200-01-P
Input Voltage	230V, 60Hz
Motor	3HP, 2250W Fan-Cooled
Amps (running)	15A
Amps (startup)	49A
Motor Speed	3450RPM
Airflow Capacity	1400 CFM
Static Pressure	12" W.G.
Operating Conditions	950ACFM @ 6" W.G.
Impeller	12.75in / 305mm
Hose Size	6in / 153mm
Height	72"/1.8m
Weight	123lbs / 56kg
Circuit Breaker Required	20A / 240V
Connector (plug)	NEMA 6-20P
Sound Rating	80 Db
Included Filter Bags	70 Micron, 40 Micron
Certifications	CSA

T2 TRIM SAVER ACCESSORIES & COMPONENTS

40 Micron Bag	23-0101-00
70 Micron Bag	23-0162-00
6" Hose - 6' Long	23-0199-00
6" Hose Cuff	23-0132-00
Vacuum Bypass T2	23-0255-00
Gasket (Stainless Bin Lid)	23-0244-00
Gasket (10" separator for Cyclone)	23-0240-00
Gasket (8" separator for cyclone)	23-0241-00
Gasket (cyclone outlet)	23-0251-00
Gasket (filter adapter)	23-0230-00
Stainless Steel Bin & Upgrade Kit	23-0425-00
Cyclone Cleaning Upgrade Kit	23-0264-00

Visit twistertrimmer.com or call your Twister Rep for an extensive list of replacement parts or accessories.

