EUROPEAN MODEL



#1 Trimming System Among **Commercial Producers**

| T2 | Туре | Feed (lbs/hr) | Feed (kg/hr) |
|----|------|------------------|-----------------|
| 1 | Wet | Up to 35 | Up to 16 |
| 2 | Wet | Up to 78 | Up to 36 |
| 3 | Wet | Up to 124 | Up to 56 |
| 4 | Wet | Up to 172 | Up to 78 |
| 1 | Dry | Up to 11 | Up to 5 |
| 2 | Dry | Up to 25 | Up to 12 |







T2 Trimmer Features

- Large-Commercial Scale
- Harvest size: ~100+lbs
- Start with Tandem scale up to Triple
- Continuous flow and runtime
- 304 stainless steel tumbler to mitigate risk of contamination
- Nitrided steel blades increase strength and resistance and decrease buildup
- Minimal handling >1 min in tumbler
- Watertight electrical and motors allow for a complete high-pressure washdown
- Wheels allow for easy transport whether indoor or outdoor



EUROPEAN MODEL







| | Product Number | 24-9025-02 |
|----------------|----------------------------|------------------|
| SPECIFICATIONS | Input Voltage | 230V, 50Hz |
| | Current Draw | 8A |
| | Blade Motor | 1HP, 750W |
| | Tumbler Diameter | 6in / 10.1cm |
| | Tumbler Slots | 50 x .25in/.3cm |
| | Cut Height | .040in / 1mm |
| | Weight | 215lbs /97.5kg |
| | Shipping Weight (w/ T2-LC) | 420lbs / 190kg |
| S | Length | 42.5in / 107.9cm |
| | Width | 27.5in / 69.9cm |
| | Height | 32.5in / 82cm |
| | Circuit Breaker Required | 10A / 230V |
| | Connector (plug) | CEE 7/7 |

| TS | T2 Leaf Collector | 23-0117E-00-P |
|--------------------------|-----------------------------|---------------|
| ACCESSORIES & COMPONENTS | T2 Trim Saver | 23-0200-01-P |
| | T2 Rail (Single) | 24-0400-00-P |
| | T2 Rail Extension | 24-0401-01-P |
| | Feed Conveyor (Inbound) | 26-0001E-01 |
| AC | Quality Conveyor (Outbound) | 26-0002E-01 |



TESTED

ADDITIONAL REQUIREMENTS Extension Cord

12 AWG (Minimum AWG Size)

7.6m / 25ft max length

CONNECTOR (PLUG)



Visit <u>twistertrimmer.com</u> or call your Twister Rep for an extensive list of replacement parts or accessories.

