

# TWISTER

# T2

## #1 Trimming System Among Commercial Producers

T2	Type	Feed (lbs/hr)	Feed (kg/hr)
1	Wet	Up to <b>35</b>	Up to <b>16</b>
2	Wet	Up to <b>78</b>	Up to <b>36</b>
3	Wet	Up to <b>124</b>	Up to <b>56</b>
4	Wet	Up to <b>172</b>	Up to <b>78</b>
1	Dry	Up to <b>11</b>	Up to <b>5</b>
2	Dry	Up to <b>25</b>	Up to <b>12</b>



## T2 Trimmer Features

- Large-Commercial Scale
- Harvest size: ~100+lbs
- Start with Tandem scale up to Triple
- Continuous flow and runtime
- 304 stainless steel tumbler to mitigate risk of contamination
- Nitrided steel blades increase strength and resistance and decrease buildup
- Minimal handling >1 min in tumbler
- Watertight electrical and motors allow for a complete high-pressure washdown
- Wheels allow for easy transport whether indoor or outdoor



# TWISTER

# T2



SPECIFICATIONS	
Product Number	02-10006B
Input Voltage	120V, 60 Hz
Current Draw	15.5A
Blade Motor	1HP
Tumbler Diameter	6in / 10.1cm
Tumbler Slots	50 x .25in/.3cm
Cut Height	.040in / 1mm
Weight	215lbs /97.5kg
Shipping Weight (w/ T2-LC)	420lbs / 190kg
Length	42.5in / 107.9cm
Width	27.5in / 69.9cm
Height	32.5in / 82cm
Circuit Breaker Required	20A / 120V
Connector (plug)	NEMA 5-20P
Certifications	CSA, UL

Extension C

ACCESSORIES & COMPONENTS	
T2 Leaf Collector	23-0117-00-P
T2 Trim Saver	23-0200-01-P
T2 Rail (Single)	24-0400-00-P
T2 Rail Extension	24-0401-01-P
Feed Conveyor (Inbound)	26-0001-02
Quality Conveyor (Outbound)	26-0002-02



TESTED

ADDITIONAL REQUIREMENTS

12 AWG (Minimum AWG Size)

7.6m / 25ft max length

CONNECTOR (PLUG)

NEMA 5-20P

Visit [twistertrimmer.com](http://twistertrimmer.com) or call your Twister Rep for an extensive list of replacement parts or accessories.

